15

20

25

WHAT IS CLAIMED IS:

1. A noise protection sheet stuck on electronic components loaded on a circuit board to supress noise generated from the electronic components, comprising:

a metallic sheet, and

insulating films which sandwich the metallic sheet in-between thereof, wherein

said metallic sheet has at its one end, an extending portion to be connected to a grounding terminal on the circuit board.

- 2. A noise protection sheet according to claim 1, wherein said metallic sheet has a first area covered with said insulating films and a second area forming the extending portion, said second area being externally exposed.
- 3. A noise protection sheet according to claim 1 or 2, wherein said extending portion has a through-hole through which a solder fillet formed on a land serving as said grounding terminal elutes when said extending potion is soldered on said land.
- 4. A noise protection sheet according to claim 1 or 2, wherein said extending portion is formed in a bent shape so as to fit a shape of at least one of said electronic components when the noise protection sheet is stuck on said electronic components.
- 5. An apparatus for mounting a noise protection sheet on electronic components loaded of a circuit board, the noise protection sheet comprising a

Soft of

metallic sheet and insulating films sandwiching said metallic sheet in-between, further comprising:

carrying means for carrying said noise protection sheet held on a carrier tape;

moving means for chucking said noise protection sheet and moving it from the carrier tape onto the electronic components on said circuit board; and soldering means for soldering an extending portion formed at the one end of said metallic sheet to a grounding terminal of said circuit board.

5

6. A method for mounting an noise protection sheet on an electronic components loaded on a circuit board, the noise protection sheet comprising a metallic sheet and insulating films sandwiching said metallic sheet in-between, comprising the steps of:

carrying said noise protection sheet held on a carrier tape;

chucking said noise protection sheet and moving it from the carrier tape onto the electronic component on said circuit board; and

soldering an extending portion formed at the one end of said metallic sheet to a grounding terminal of said circuit board.

thermal plastic of rothe colice